

00 :

TBT-09H & NBSP; 000 00 000 & NBSP; & nbsp; & nbsp; 00 000 00 00 00, 00 00, 0 00 00 0 000 00,
0 0 00 00 00, 000 00000 00 achievemest 000 000 000 000 00,,; 00 00 0

00 :

- 1 & NBSP; & NBSP; 00 00 : -50 °C ~ + 300 °C (-58 °F ~ 572 °F);
- 2 & NBSP; 00 000 : 000000 + 0.1degree; -20 °C ~ 100 °C (-4 ° F ~ 212 ° F) : + -1 °C,
100 °C ~ 200 °C (212 ° F ~ 392 ° F), -20 °C ~ -40 °C (-4 ° F ~ -40 ° F) : + -2 °C,
200 °C ~ 300 °C (392 ° F ~ 572 ° F) - 40 °C ~ -50 °C (-40 ° F ~ -50 ° F) : + -2 °C ~ + -5 °C
- 3 & NBSP; & NBSP; LCD 000000 00 0;
- 4 & NBSP; & NBSP; 0 00 0 00.
- 5 & NBSP; & NBSP; 000000 00 00 00;
- 6 & NBSP; & NBSP; °C / 0000 00 °F;
- 7 & NBSP; & NBSP; 12000 75 / 200mm 00 00.
- 8 & NBSP; & NBSP; 00 00 00.