

TL-302 0000 0000 00 00 0, 0000 00 0

sepciations:

00 00: 50oc 0 (32 122of)

00 00: 10 ~ 90% RH

00 00: -10 ~ 60oc (14 ~ 140of)

00 00: 10 75% RH

00: 110 * 45 * 20mm

00: 60g (0000 00)

00: 00 00 0000 0000

00 00: 1m/s 0 ~ 30 0.1

ft/min 0 ~ 5860 19

00 0 ~ 55 0.2 ± 5%

km/h 0 90 0.3

mph 0 65 0.2

00 00: oC 0 ~ 30m/s,-45 ~ 10 0.1 1

0 ~ 65 mph,-49 50 0.1 1.8

00: 70 0.1 1 0C-29

-20 ~ 158 0.1 1.8

00 00:% RH 0 ~ 100 0.1 ± 3%

00 0 0: oC 0 ~ 100% RH, 21.1 ~ 54.4 0.1 2

0 ~ 100% RH, 70 ~ 130 0.1 3.6

000: 70 0.1 2 0C-29

-20 ~ 158 0.1 3.6

0 0: hpa 10 1100 0.1 1.5

mbar 10 ~ 1100 0.1 1.5

inhg 0.29 32.48 0.01 0.05

00: m-700 ~ 9000 1 12

ft-6000 ~ 3 1 50

00 00: 50oc 0 (32 122of)

00 00: 10 90% RH

00 00:-10 60oc (14 140of)

00 00: 10 75% RH

siz: e 110 * 45 * 20mm

00: 60g (0000 00)