

## **Specifications**

1. Total Range 30 to 130dB
2. Maximum Level 130dB
3. Accuracy  $\pm 1.5$ dB
4. Range Selections 30 to 80dB, 50 to 100dB, 60 to 110dB, 80 to 130dB
5. Frequency Range 31.5Hz to 8000Hz
6. Frequency Weighting A and C
7. Time Weighting FAST (125ms)
8. SLOW (1 second)
9. Analogue Bar Graph 30~130dB
10. Warning Over-Range "OVER", Under-Range "UNDER"
11. Analogue Outputs AC: 0.707Vrms full scale; Output impedance: around 600 $\Omega$
12. DC: 2Vrms full scale; 10mV/dB; Output impedance around 100 $\Omega$
13. Max/Min Mode
14. Data Hold
15. Display Backlight
16. Sleep Mode
17. Low Battery Display 4.8V
18. Power 1.5V Battery (AA) x 4
19. LCD Size 53 x 41mm
20. Product Color Red and Grey

## **Packing Info**

1. Product Size 273 x 70 x 39mm
2. Standard Carton Measurement: 670 x 385 x 300mm(0.077 CBM Per Standard Carton)
3. GW :18 kg
4. Standard Accessories Batteries, English Manual Standard Individual Packing Gift Box