GM610 Mood Moisture Meter,timber moisture meter,moisture content meter,wood moisture content

Specification

Measuring range2~40%/50%/60%/70%
Resolution: 0.5%
Temperature range: -10~60℃
Humidity range: 20%RH~95%RH
Moisture response speed: <1s
Measure error: ±1%
Display: LCD
Operating environment: Temperature:0~40℃
Humidity:20%~95%RH
Power: 2*1.5V AAA battery
Unit size: 135.6*55*29.4,
278*36*36mm(Testing handle probe)

Testing range	type of wood	Testing range	type of wood
2~40%：	Rhodes west teak	2~60%	Banya pine
	Ormosia hosiei		Douglas fir / D-fir
	Brazil walnut tree		Lauan
2~50%：	Walnut tree		Manchurian ash
	Apitong		European silver
	White poplar		Maple
	Teak		White ash
2~70%	Chinese red pine		African whitewood
	Coquito		Rose wood
	Abies holophylla maxim		Elm tree
	Larch		Gmelina chinensis benth
	Apitong		Hemlock
	Birch		Dipterocarpus
	Basswood		Oak

Payment Methods:

We accept TT bank wire transfer, Western Union, Paypal and escrow payment offered by Alipay Escrow and Escrow.com.

For latter three payment methods, extra charges shall be applied.

Shipping Methods:

To be shipped by express mail, by air or by sea based on customer’s request and weight/volume of goods.

Warranty:

We provide a limited quality warranty of 12 months for the items sold dating from their delivery date.