

BW-400 X USB 2.0 4 X 400 X 400

특징:

4 X 400 X 400
4 X 400 X 400 (4 X 400 X 400)
4 X 400 X 400
4 X 400 X 400
4 X 400 X 400
USB 2.0 4 X 400 X 400
AP 400: 400 X 400, 400 X 400

주요 특징:

400: 400, 400, 400, 400... 400 X 400.
400 X 400: 400 X 400.
400 X 400.
400 X 400: 400 X 400 X 400 X 400
400 X 400 X 400.
400: 400, 400, 400...
400 X 400: QC 400 X 400.
400 X 400: 400 X 400 X 400, 400 X 400.
PCB 4 SMT 400 X 400
400: 400 & 400 X 400.
400 X 400: 400 X 400 X 400.
400 X 400.

특징:

400 X 400: 400 X 2m X 400
400 X 400: 400 X 400 DSP (400 X 400 X 400)
400: 400 X 400 X 400 X 2m X 400
400 X 400: 0mm ~ 40 mm
400 X 400: 400 X 400 X 400
400 X 400 X 400: 1600 * 1200, 1280 * 1024, 800 * 600, 640 * 480, 352 * 288, 320 * 240, 176 * 144
400: 400 X 400 X LED x8 PC
400 X 400 X 400: 5M, 3m, 2 M, 1.3 M, VGA
400 X 400: 30 f/s 600 X 400 (1.3 M) X 400
400 X 400: 4x 400 X 400
400 X 400: 400 X 400, 400 X 400 X 400 W/B
400 X 400: 25 X ~ 400 X (400 X 400)
USB 400 X 400 X 400: DC 5V
400 X 400: USB 2.0
400 X 400: 400 X 400 XP, 400 X 400, 400 X 7 32 X 400 X 64 X 400.
400 X 400: 400, 400, 400, 400, 400, 400, 400, 400
400 X 400 X 400: 400 X 400 700 M Hz & 400, 1 G HD 400 X 400 CD, 512MB RAM, 400 X VGA 400
CD 400: 400 X 400
400 X 400: 400 X 400 X 400 X 400 X 400 X 400
400: 113 m m (L) X 33 mm (R)
400: 325 g