

K002 鋼 鋼 鋼 鋼 鋼 鋼 鋼

鋼:

34 * 10mm 鋼 LCD 鋼鋼鋼.
鋼 鋼 鋼 鋼 鋼鋼鋼 鋼鋼, 鋼, portable 鋼 鋼 鋼.
mm 鋼 鋼 鋼 鋼 鋼鋼.
鋼鋼 鋼鋼鋼 0鋼 鋼 鋼鋼.
鋼 鋼 鋼 (0-150mm), 鋼 鋼鋼 鋼 鋼鋼.
鋼, 鋼, 鋼, 鋼, 鋼 鋼 鋼鋼 鋼鋼 鋼鋼 鋼 鋼, 鋼.

鋼:

鋼: 鋼 鋼 鋼鋼
鋼 鋼: 0-150mm/0-5.9鋼
鋼鋼: 0.1 mm/0.01鋼
鋼鋼: ± 0.2 mm/0.01 in
鋼: 1 * 1.5 v SR44/LR44 鋼 鋼鋼 (鋼 鋼 鋼)
鋼 鋼: 0-40 ° c
鋼 鋼: -20-70 ° c
鋼鋼 鋼: $\leq 80\%$
鋼 鋼: 24 * 7.7 * 1.2 c m/9.4 * 3 * 0.5鋼
鋼 鋼: 61g/2.2 鋼
鋼 鋼: 28.5 * 9.8 * 1.3 c m/11.2 * 3.9 * 0.5 in
鋼鋼 鋼: 90g/3.2 鋼