



RAD-30 MODEL X-y 0000 000000. 00 0000 GAMM 00 0000 00 0 0 00000. 00 00, X 0, 00000 00000 0 00 00  
 0 characteristics.Using. 0000 00 00 00 000000.



- 00 0000 00 00 0000 00 1. 00;
- 00 00 00 00 00 2. 00;
- 00 00 00 00 0000 00 3;
- 00 00 00 00 00 4. 00;
- 5. 0000 00 (00).



- 00 0000 00 0 1 0000 00
- 2. 00 00 0000 00 00
- 3. 00 0000 00 00
- 4. 00, 00 00 0000 00
- 5. 00 00 00000 00
- 6. 00 X, 00 0000 00
- 7. 0000 00 0000 0000 00
- 8. 0000 00, 00 0000 00 0000 0000 00
- 9. 0000 0000 0000 00



- 1. 0 00 0000 LCD 000000 00000;
- 2. 00 00, 00 0000 0000 00 0000;
- 3. 0000 00 0000 00 00 00
- 00 00 0 00 4. 00 00;
- 5. 00 0000 0 0000 00
- 00 00 0 00 6. 00 00;
- 7. 00 00 00 000000.
- 8. 00000 0000 00 0 00 00 00 00 00 0
- 9. 00000 00, 00 00 00 00
- 10. 0000 00 0 0000 00 00;
- 11. 00 00 00 00



- 1. 00 00 :  
 0000 0000 00 (137Cs) : 0.01 00000 0000 / 00 ~ 100mSv / h  
 00 00 (137Cs) : 0.01uSv ~ 9999Sv
- 2. 0000 00 :  
 X 0 00 0000 : 40Kev ~ 3.0Mev  
 (137Cs 000000) ≤ ± 25 % 3. 0000 0000
- 4. 00 00 : ± 10 % ≤ (20uSv00 / 00)
- 5. 0000 00 00 00 0 : 00 0000 0000 0000
- 6. 00 00 00 00 :0000 3 0 00 (10 USV / H)
- 7. 000000 00 :  
 00 00 : USV / H, mSv / H, SV / 00 00 00  
 00 0 : USV, mSv, Sv 00 00

8. □□□ : □□□ AAA □□□

9. □□ □□ □□ :  $-20^{\circ}\text{C} \sim +50^{\circ}\text{C}$