#### ET-965 5 In 1 Multifunctional Environment Meter



# **Description**

- 1. 5 in 1 for Light meter, Sound level meter, Humidity meter, Temperature meter and Anemometer
- 2. Data Hold and Max Hold

## **Features**

- 1. 5 in 1 for Light meter, Sound level meter, Humidity meter, Temperature meter and Anemometer
- 2. Large backlit LCD display
- 3. Data Hold and Max Hold
- 4. Overrange indication
- 5. Low battery indication



# **Specifications**

Sound Level				
Applied standard	IEC61672-1 CLASS2			
Accuracy	± 2.0dB			
Display	4digts			
Resolution	0.1dB			
Frequency response	31.5Hz ~ 8kHz			
Measurement range	Auto: 35dB ~ 130dB			
Frequency weighting	dBA			
Microphone	1/2 inch Electric condenser microphone			
Light				
Measuring range	0 Lux ~ 200K Lux, 0Fc ~ 20KFc			
Spectral response	CIE photopic (CIE human eye response curve)			
Spectral accuracy	CIE Vλfunction f1 '& lt; = 6%			
Cosine response	f2 '& lt; = 2%			
Accuracy	$\pm$ 4% rdg $\pm$ 0.5% f.s (& lt; 10,000Lux). $\pm$ 5% rdg $\pm$ 10dgts (& gt; 10,000Lux).			

Photo detector	One silicon photo diode with filter			
Air velocity				
Air velocity range	0.5m / s ~ 30.0m / s			
Air velocity accuracy	± (3% ± 0.3d)			
Measurement units	m / s, km / h, ft / min, knots, Mph,			
Temperature				
Measurement range	-40 ~ 70 ° C (-40 ~ 158 ° F)			
Accuracy	± 2.0 ° C, ± 3.6 ° F			
Measurement units	° C / ° F			
Resolution	0.1			
Humidity				
Measurement range	10 ~ 95% RH			
Accuracy	± 5RH%			
Resolution	0.1			
Data update	1 time / sec			
Maximum value	MAX			
Minimum value	MIN			
Data Hold	HOLD			
Auto power off	Automatically power off after approx. 15 minutes of inactivity			
Power supply	one 9V battery with type of 006P, NEDA1604 or IEC6F22			
Battery life	About 30 hours			
Operating condition	-20 ° C ~ 60 ° C, 10% RH ~ 90% RH			
Storage condition	-40 ° C ~ 60 ° C, 10% RH ~ 75% RH			
Dimensions	252 (L) * 66 (W) * 33 (H) mm			
Weight	568g			

#### **Package information**

1. Package: Carrying case with gift box

2. PCS / CTN: 5pcs / inner carton; 10pcs / master carton

3. Master Carton Measurements: 76 \* 49 \* 34CM

4. Gross Weight: 17.5KG

5. Sample Lead Time: 3-5days

6. Production Lead Time: 30days

7. Warranty: one year

### **Payment Methods:**

We accept TT bank wire transfer, Western Union, Paypal and escrow payment offered by Alipay Escrow and Escrow.com.

For latter three payment methods, extra charges shall be applied.

#### **Shipping Methods:**

To be shipped by express mail, by air or by sea based on customer's request and weight / volume of goods.

#### **Warranty:**

We provide a limited quality warranty of 12 months for the items sold dating from their delivery date.