

GM610 **Mood Moisture Meter**,timber moisture meter,moisture content meter,wood moisture content



Specification

Measuring range□2~40%/50%/60%/70%

Resolution: 0.5%

Temperature range: -10~60°C

Humidity range: 20%RH~95%RH

Moisture response speed: <1s

Measure error: ±1%

Display: LCD

Operating environment: Temperature:0~40°C

Humidity:20%~95%RH

Power: 2*1.5V AAA battery

Unit size: 135.6*55*29.4,

278*36*36mm(Testing handle probe)

Testing range	type of wood	Testing range	type of wood
2~40% :	Rhodes west teak	2~60%	Banya pine
	Ormosia hosiei		Douglas fir / D-fir
	Brazil walnut tree		Lauan
2~50% :	Walnut tree		Manchurian ash
	Apitong		European silver
	White poplar		Maple
	Teak		White ash
2~70%	Chinese red pine		African whitewood
	Coquito		Rose wood
	Abies holophylla maxim		Elm tree
	Larch		Gmelina chinensis benth
	Apitong		Hemlock
	Birch		Dipterocarpus
	Basswood		Oak



Payment Methods:

We accept TT bank wire transfer, Western Union, Paypal and escrow payment offered by Alipay Escrow and Escrow.com.

For latter three payment methods, extra charges shall be applied.

Shipping Methods:

To be shipped by express mail, by air or by sea based on customer's request and weight/volume of goods.

Warranty:

We provide a limited quality warranty of 12 months for the items sold dating from their delivery date.