

## Sound & Light Alarm Hygro-thermometer A2000-EX

### Features:

Sound & light alarm if user defined high/low values are exceeded.  
Deviation manual calibration  
External sensor could expand length to 50 meters.  
Could add external sound & light alarm.  
Could add delay alarm function, if the data exceed limit and return to normal within the delay time, the device will not alarm.  
Display temperature, humidity, time as well as environment status simultaneously  
MAX/MIN function key to show the maximum/minimum value  
Desk-top placing or Wall Hanging.

### Specifications

Temperature Accuracy  $\pm 0.5^{\circ}\text{C}$   
Humidity Accuracy  $\pm 5\%\text{RH}$   
Temperature Measurement Range  $-40 \sim +85^{\circ}\text{C}$   
Humidity Measurement Range  $0 \sim 100\%\text{RH}$   
Resolution  $0.1^{\circ}\text{C} / 0.1\%\text{RH}$   
Sensor type External sensor with 3 meters cable  
Battery 9V Block Battery \*1  
Alarm Buzzer and light  
Dimensions  $135\text{mm} * 124\text{mm} * 35\text{mm}$  (5.31" \* 4.88" \* 1.37" inch)  
LCD display area  $97\text{mm} * 78\text{mm}$  (3.81" \* 1.37")  
Weight 330g  
Certificate CE, ISO  
Accessories 9V Block Battery, user manual, screw