

Quick Details

- Place of Origin: Guangdong, China (Mainland)
- Brand Name: Neutral
- Model Number: XYI-III

Packaging & Delivery

Packaging Details: Dimension: 135 (L) x72 (W) x33 (H) mm

Delivery Detail: 3-30days

Specifications

Digital Light Level Meter XYI-III

XYI-III digital light meters

The XYI-III All Digital Luxmeter is based on all digital integral photometric measurement technology. It has no analogue unit, thus it is very simple to overcome the zero drift which is impossible to be avoided in current Luxmeter. The digital V(l) sensor has large dynamic range so that there is no range-changing error in it, moreover, it possesses strong anti-interference ability and high accuracy. The XYI-III All Digital Luxmeter contains RS232 computer interface, the calibration is done by software. It is suitable for monitoring and remote applications. The XYI-III All Digital Luxmeter software can calibrate the instrumentation, sample the data through RS232 interface and print out the results. It is a real-time measuring system and run under Windows98/NT.

digital light meters

Specification:

Dynamic range: 0.1--100,000 lx
Accuracy: $<\pm 4\%$
Sensitivity: 0.001 lx
Repeatability: 0.001 lx
Relative spectral sensitivity of digital V(l) sensor: $f1 < \pm 5.5\%$
Direction response: $f2 < \pm 4\%$
Infrared response: $f3 < \pm 2\%$
Ultraviolet response: $f4 < \pm 1.5\%$
Fatigue: $f5 < \pm 0.5\%$
Nonlinear error: $f6 < \pm 1\%$
One range, no range-changing error, $f7 = 0$
Temperature effect: $\pm 0.5\%/^{\circ}\text{C}$
Refreshing frequency: 3n/s($\geq 1\text{lx}$), 1n/2s($< 1\text{lx}$)
3-1/2 LCD display
RS232 computer interface and software
Power supply: 9V Battery
Size(L×W×H): 135×72×33(mm)

digital light meters